


Spring plunger, with spring loaded ball, with slot, standard spring force



2471.05.



Material:

Sleeve: Delrin blue (POM)
Ball: Delrin white (POM)
Spring: Nirosta

Note:


For locking and for pressing upwards or downwards.
Temperature operating range: -30°C to +50°C

2471.05. Spring plunger, with spring loaded ball, with slot, standard spring force

| Order No | d ₁ | l | s | d ₂ | Spring force [N] | |
|-------------|----------------|----|-----|----------------|------------------|-------|
| | | | | | initial | final |
| 2471.05.006 | M6 | 14 | 0.9 | 3.5 | 12 | 17 |
| 2471.05.008 | M8 | 16 | 1.5 | 5 | 20 | 35 |
| 2471.05.010 | M10 | 19 | 1.9 | 6 | 25 | 45 |



2471.35.



Material:

Sleeve: Delrin blue (POM)
Ball: Nirosta, hardened
Spring: Nirosta

Note:

For locking and for pressing upwards or downwards.
Admissible temperature range: -30°C to +50°C.

2471.35. Spring plunger, with spring loaded ball, with slot, standard spring force

| Order No | d ₁ | l | s | d ₂ | Spring force [N] | |
|-------------|----------------|----|-----|----------------|------------------|-------|
| | | | | | initial | final |
| 2471.35.006 | M6 | 14 | 0.9 | 3.5 | 12 | 17 |
| 2471.35.008 | M8 | 16 | 1.5 | 5 | 20 | 35 |
| 2471.35.010 | M10 | 19 | 1.9 | 6 | 25 | 45 |