


Spring plunger, with spring loaded pin, with hexagon socket, standard spring force

2472.03.



2472.03. Spring plunger, with spring loaded pin, with hexagon socket, standard spring force

Order No	d_1	d_2	l	s	A/F	Spring force [N]	
						initial	final
2472.03.004	M4	1.8	12	1.5	2	4.5	12.5
2472.03.005	M5	2.4	14	2	2.5	5	13
2472.03.006	M6	2.7	15	2	3	6	17
2472.03.008	M8	3.8	18	2	4	16	33
2472.03.010	M10	4.5	23	2.5	5	19	42
2472.03.012	M12	6	26	3.5	6	22	57
2472.03.016	M16	8.5	33	4.5	8	38	78
2472.03.020	M20	10	43	6.5	10	39	81
2472.03.024	M24	13	48	8	12	72	155


Material:

Sleeve: Free machining steel, burnished
 Pin: Free machining steel hardened, burnished
 Spring: Nirosta

Note:

For locking and for pressing upwards or downwards.
 Temperature operating range: max. 250°C

2472.33.



2472.33. Spring plunger, with spring loaded pin, with hexagon socket, standard spring force

Order No	d_1	d_2	l	s	A/F	Spring force [N]	
						initial	final
2472.33.004	M4	1.8	12	1.5	2	4.5	12.5
2472.33.005	M5	2.4	14	2	2.5	5	13
2472.33.006	M6	2.7	15	2	3	6	17
2472.33.008	M8	3.8	18	2	4	16	33
2472.33.010	M10	4.5	23	2.5	5	19	42
2472.33.012	M12	6	26	3.5	6	22	57
2472.33.016	M16	8.5	33	4.5	8	38	78
2472.33.020	M20	10	43	6.5	10	39	81
2472.33.024	M24	13	48	8	12	72	155

Material:

Sleeve: Nirosta 1.4305
 Pin: Nirosta 1.4305
 Spring: Nirosta

Hinweis:

For locking and for pressing upwards or downwards.
 Admissible temperature range: max. 250°C