


Spring plunger, with spring loaded pin, with slot, increased spring force



2472.06.



Material:

Sleeve: Free machining steel, burnished
Pin: Free machining steel hardened, burnished
Spring: Nirosa

Note:


For locking and for pressing upwards or downwards.
Temperature operating range: max. 250°C
Identification of increased spring force by two longitudinal marks on the sleeve.

2472.06. Spring plunger, with spring loaded pin, with slot, increased spring force

Order No	d ₁	d ₂	l	s	Spring force [N]	
					initial	final
2472.06.006	M6	2.7	14	2	11	25
2472.06.008	M8	3.8	16	2	23	59
2472.06.010	M10	4.5	19	2.5	20	54
2472.06.012	M12	6.2	22	3.5	38	96
2472.06.016	M16	8.5	24	4.5	50	100
2472.06.020	M20	10	30	6.5	52	133
2472.06.024	M24	13	34	8	91	223



2472.36.



Material:

Sleeve: Nirosa 1.4305
Pin: Nirosa 1.4305
Spring: Nirosa

Note:

For locking and for pressing upwards or downwards.
Temperature operating range: max. 250°C
Identification of increased spring force by two longitudinal marks on the sleeve.

2472.36. Spring plunger, with spring loaded pin, with slot, increased spring force

Order No	d ₁	d ₂	l	s	Spring force [N]	
					initial	final
2472.36.006	M6	2.7	14	2	11	25
2472.36.008	M8	3.8	16	2	23	59
2472.36.010	M10	4.5	19	2.5	20	54
2472.36.012	M12	6.2	22	3.5	38	96
2472.36.016	M16	8.5	24	4.5	50	100
2472.36.020	M20	10	30	6.5	52	133
2472.36.024	M24	13	34	8	91	223